

RENKLİ WALLWASHER / DUVAR BOYAMA UYGULAMALARI

ARMATÜR

Ürün Kodu: DB-67

IP-67 Koruma
6063 Kalite eloksal kaplı Alüminyum profil
170, 325, 480, 640, 960, 1200 ve 1500 mm uzunluk seçeneği
Ekstrüzyon soğutucu
4 mm temperli cam
Fiber yan kapak ve silikon conta
Paslanmaz armatür ayağı



OSRAM DURIS® S5



Type	Wavelength	Forward Voltage (typ.)	Rth (K/W)	Typ. Luminous and Radiant Flux (lm & Mw)	Luminous (lm/W) & Radiant (%) Efficacy	Max Current
GA PSLR31.13-HUJQ-A1A2-1	610 nm (Amber)	6,25	17	45 lm	48 lm/W	150 mA
GD PSLR31.13-2T4T-25-1	450 nm (Deep Blue)	6,25	17	420 Mw	0,45 lm/W	150 mA
GR PSLR31.13-GPGR-R1R2-1	620 nm (Red)	6,25	17	22 lm	23 lm/W	150 mA
GT PSLR31.13-LSLU-T1T2-1	540 nm (True Green)	6,25	17	170 lm	181 lm/W	150 mA

LED DRIVER

Ürün Kodu: SAR-35-700 CC

PF \geq 0.9

Verimlilik: \geq 85%

IP65

Uoutput: 32-50V

3 YIL GARANTİ , LVD – EMC Test Raporları



sarNeks

LED MODÜL

Product Code	Color Temperature	Total number of LEDs	Number of parallel strings	Number of LEDs per string	Luminous Flux @ts=25°C (lm) ²		Luminous Flux @ts=65°C (lm) ²		Min.forward Voltage @ts=65°C (V) ²	Max.forward Voltage @ts=25°C (V) ²	Max. Power consumption (W) ²	Colour rendering index (CRI)
Operating mode at 350 mA												
LNR-300x16-DS5V1x12-30	3000K	12	2	6	1640,8	2034	1525,9	1891,6	33	38,4	13,44	≥80
LNR-300x16-DS5V1x12-40	4000K	12	2	6	1640,8	2034	1525,9	1891,6	33	38,4	13,44	≥80
LNR-300x16-DS5V1x12-65	6500K	12	2	6	1640,8	2034	1525,9	1891,6	33	38,4	13,44	≥80
LNR-300x16-DS5V2x12-30	3000K	12	2	6	592,2	733,2	550,7	681,9	16,5	19,8	6,93	≥80
LNR-300x16-DS5V2x12-40	4000K	12	2	6	592,2	733,2	550,7	681,9	16,5	19,8	6,93	≥80
LNR-300x16-DS5V2x12-65	6500K	12	2	6	592,2	733,2	550,7	681,9	16,5	19,8	6,93	≥80

